

ALZM03A



- Two Serial data RJ11 connectors for accessories.
- Ground closure 600mA output for optional beeper. (not included).
- Timer Construction: ABS Plastic enclosure, black.
- Display Construction: ABS Plastic enclosure, black.
- Power requirements: 10-18 VAC or 12-24 VDC power.
- Current consumption: 100ma.
- TMR218B6BK_RF2 Dimensions: 6.75" x 4.75" x 2.5".
- RYG14AB_RF2 Dimensions: 5.63" x 3.25" x 1.5".

Features:

- Count up elapsed timer settable to Hour:Min or Min:Sec.
- Count down time remaining timer settable to Hour:Min or Min:Sec.
- Easy to use. Press Reset. Turn knob to set the desired time. Press Start.
- Subsequent timing cycles. Press Reset. The time previously used will be loaded. Press Start.
- Green, Yellow and Red warning indicators have preprogrammed settings to match Toastmasters requirements, or may be programmed by user.
- Four-digit LED seven-segment Display with 0.56 inch high digits.
- Beeper provides audible sound when timer reaches zero.
- Button to turn beeper on/off.
- Connect two or more TimeKeepers™ together. One becomes the Timer, and the others become remote Displays.
- Made of ruggedized ABS plastic construction.

Product

Presentation Timer with Red-Yellow-Green

Description:

This wireless presentation TimeKeeper™ system includes a TMR218B6BK_RF2 Count Up/Down Timer with two programmable presets, and a RYG14AB_RF2 Red-Yellow-Green LED Display that is visible to the speaker and the audience.

Item: ALZM03A

UPC: 788581650035

EAN: 0788581650035

Stock Status: Usually in stock.

Dimensions: 6.75" x 4.75" x 2.5"

Weight: 4.1 lbs.

MSRP: \$997.00

Specifications:

Item Includes:

- (1) TMR218B6BK-RF2 Wireless Count up/down timer.
- (1) RYG14AB-RF2 Indicator lamp module with wireless transceiver.
- (2) WTAEC-4875 7.5VDC Wall adapter.
- (1) RC Reference card.
- (1) WD Wiring diagram.

Optional Accessories:

- (1) DSP254B Large LED wall display.