

ALZML08A



Product

Presentation Timer w/ Large LED Display

Description:

This presentation TimeKeeper™ system includes a KP215ASM Count Up/Down Timer with three programmable presets, and a DSP504B Large Four-digit LED wall Display visible (up to 100ft) to the speaker and the audience.

Item: ALZML08A

UPC: 788581652312

EAN: 0788581652312

Stock Status: Usually in stock.

Dimensions: 21.5" x 8" x 2.5"

Weight: 8.1 lbs.

MSRP: \$649.00

Specifications

- Two Serial data RJ11 connectors for accessories.
- One RS422 output with RJ45 connector for accessories.
- Ground closure 600mA output for optional beeper. (not included).
- Timer Construction: Metal enclosure, black powder coated finish.

- Display Construction: Metal enclosure, black powder coated finish.
- Power requirements: 10-18 VAC or 12-24 VDC power.
- Current consumption: 500ma.
- KP215ASM Dimensions: 2.85" x 1.8" x 1.32".
- DSP504B Dimensions: 21.5" x 8" x 2.5".

Mounting methods

- Standard mounting is 2 key hole slots spaced 16inch apart for wall mounting.
- There are screws at either end of the displays where D-Rings can be added. D-Rings are NOT included and may be ordered separately.
- 1/4-20 nuts on the bottom of the unit for attaching a tripod adapter or feet. The feet and tripod adapter is NOT included and may be ordered separately.
- The display has holes in the top for adding a handle. The handle is NOT included and may be ordered separately.

Features

- Count up elapsed timer settable to Hour:Min or Min:Sec.
- Count down time remaining timer settable to Hour:Min or Min:Sec.
- Easy to use. Press Reset. Turn knob to set the desired time. Press Start.
- Subsequent timing cycles. Press Reset. The time previously used will be loaded. Press Start.
- Green, Yellow and Red warning indicators have preprogrammed settings to match Toastmasters requirements, or may be programmed by user.
- Four-digit LED seven-segment Display with 0.56" high digits.
- Beeper provides audible sound when timer reaches zero.
- Button to turn beeper on/off.
- Built in Time of day clock displays 12 or 24 hour mode.
- Connect two or more TimeKeepers™ together. One becomes the timer, and the others become remote displays.
- Made of ruggedized aluminum construction.

In the Box

- KP215ASM Count up/down timer
- DSP504B Large LED display
- WT12VAC1200MA-RA 12V AC, 1200 MA Transformer.
- M8BK025F 25ft Cable, CAT-5.
- RC Reference guide
- WD Wiring diagram

Optional Accessories

- RYG11ABBK Red-yellow-green indicator lamps

- RYG400AB Red-yellow-green indicator lamps