

SPE3603SW



Product

LED Display, 36" Digits

Description:

Three-digit Race Clock with 36" high super bright red LED digits, with handle and feet, water resistant enclosure and an internal RF wireless transceiver, metal frame. Includes Wireless Keypad.

Item: SPE3603SW

UPC: 788581656273

EAN: 0788581656273

Stock Status: Special order item. Allow 12 weeks lead time.

Dimensions: 96" x 48" x 7"

Weight: 240 lbs.

MSRP: \$5,194.00

Specifications

- (1) 900MHz RF Wireless communications interface.
- (1) 7-Way Trailer connector for RS422 serial data input.
- (1) 7-Way Trailer connector for RS422 serial data output.
- (1) 7-Way Trailer connector for power.
- (1) Power requirements: 12-15VDC.
- (1) Current consumption: 3.5A maximum per digit.
- (1) Construction: ABS Plastic enclosure with transparent red acrylic front.
- (1) Installation options: Unistrut mounting brackets are included. You provide your own unistrut and unistrut hardware for installation.

Features

- (1) Two-digit count up timer settable to Day, Hour, Min or Sec.

- (1) Two-digit count down timer settable to Day, Hour, Min or Sec.

Common Features

- (1) 900MHz RF wireless keypad (KP217A) permits the displays to be controlled remotely.
- (1) RF wireless module permits the displays to be controlled remotely.
- (1) History memory records the 64 most recent events.
- (1) Connect two or more TimeKeepers™ together. One becomes the 'Timer' and the others become 'Remotes'.
- (1) Two-digit count up timer settable to Day, Hour, Min or Sec.
- (1) Two-digit count down timer settable to Day, Hour, Min or Sec.
- (1) Construction: Metal enclosure with transparent red acrylic front. Includes a handle and feet.
- (1) When used with a KP219 Keypad:.
- (1) Count Up Timer (0 to 99:59.59 MM:SS.HH or 0 to 99:59:59 HH:MM:SS) with ground closure inputs or optional Start, Stop and Reset buttons.
- (1) Count Down Timer (99:59:59 to 0 HH:MM:SS).
- (1) Built-in time-of-day clock displays hours/minutes in 12/24 hour time or minutes/seconds.

Item Includes

- (1) DSP3603B Large LED display
- (1) RC Reference card
- (1) WD Wiring diagram
- (1) DSP204B6-TMR Count Up/Down timer with integrated 900MHz wireless module.
- (1) KP217A 900MHz RF wireless keypad (KP217A) permits the displays to be controlled remotely.
- (1) PS25A14V Power supply: 14.1 VDC, 25 Amp power supply (SS-30DV).
- (1) ZZXX Cable from the DSP204B6 to the display.
- (1) ZZXX Cable from the power supply to the display.
- (1) ZZXX Cable from the AC wall outlet to the power supply.
- (1) Not Included: Unistrut and mounting hardware.