

ALZP001A



Product

Production Monitor with TAKT Timer

Description:

Production monitoring system featuring TAKT Timer/Counter and Quad Display with 1" high digits in a common enclosure. Displays Target, Actual, Deviation and Efficiency.

Item: ALZP001A

UPC: 788581652763

EAN: 0788581652763

Stock Status: Usually in stock.

Dimensions: 10" x 8" x 2.5"

Weight: 8.3 lbs.

MSRP: \$1,249.00

Specifications

- (1) Serial data RJ11 connectors for accessories.
- (1) Display has RS422 output with RJ45 connector for accessories.
- (1) Construction: Metal enclosure, black powder coated finish.
- (1) Power requirements: 10-18 VAC or 12-24 VDC power.
- (1) Current consumption: 600ma.

- (1) TMR223B9_PROD1 Dimensions: 4.5" x 4.5" x 1.25".
- (1) KP04BOC_SM Dimensions: 3.5" x 1.75" x 1".
- (1) Four DSP104B displays in a common enclosure.
- (1) DSP1016B0 Labels: Target, Actual, Deviation, Efficiency.
- (1) DSP1016B0 Dimensions: 10" x 8" x 2.5".

Features

- (1) Easy to use. Press Reset. Turn knob to set the desired time. Press Start.
- (1) Subsequent timing cycles. Press Reset. The time previously used will be loaded. Press Start.
- (1) Actual time to build elapsed Timer.
- (1) TAKT Timer to set the pace.
- (1) Green, Yellow and Red warning indicators have preprogrammed default settings, or may be custom programmed by user.
- (1) Four-digit LED seven-segment Display with 1" high digits.
- (1) Count up timer actual timer displays Hour:Min or Min:Sec.
- (1) TAKT timer settable to Hour:Min or Min:Sec.
- (1) Displays may be custom configured to show Target, Actual, Deviation Efficiency, TAKT time, Actual Time and other parameters.
- (1) Made of ruggedized aluminum construction.
- (1) Beeper provides audible sound when TAKT time expires.
- (1) Button to turn beeper on/off.

Item Includes

- (1) TMR223B9-PROD1 Production monitoring TAKT time controller.
- (1) KP04BOC-SM Keypad with four buttons.
- (1) DSP1016B0 Quad 4-Digit LED displays with 1" high digits in a common enclosure.
- (1) M6X002F RJ11, Six conductor crossover phone cord, 2ft.
- (1) M4C007F RJ11, Four conductor standard phone cord, 7ft.
- (1) WT12VAC1200MA-RA 12V AC, 1200mA transformer
- (1) RC Reference card
- (1) WD Wiring diagram