

ALZP003A



Product

Production Monitor with TAKT Timer

Description:

Record actual production count, production goal, deviation and production efficiency. Also display TAKT times and record historical data that will be automatically uploaded to the Alzacloud service for future data analysis. Production monitoring system featuring TAKT Timer/Counter and Quad Display with 4" high digits in a common enclosure. Displays Target, Actual, Deviation and Efficiency.

Item: ALZP003A

UPC: 788581656488

EAN: 0788581656488

Stock Status: Usually in stock.

Dimensions: 27" x 15" x 2.5"

Weight: 12.3 lbs.

MSRP: \$2,249.00

Specifications

- Display has RS422 output with RJ45 connector for accessories.
- Construction: Metal enclosure, black powder coated finish.
- Power requirements: 10-18 VAC or 12-24 VDC power.
- Current consumption: 600ma.
- DC417B6_PROD1 Dimensions: 6.4" x 3.7" x 2.5".
- KP04B_OC Dimensions: 3.5" x 1.75" x 1".
- Quad DSP404B displays in a common enclosure.
- Display Includes Loud Beeper.
- DSP404X4B Dimensions: 27" x 15" x 2.5".
- DSP404X4B Labels: Target, Actual, Deviation, Efficiency.

Features

- Production Monitoring With Ethernet for cloud Storage.
- Programmable TAKT Timer and Scale Count.
- Running or Static/Shift Goals.
- Monitor and Save Production Data.
- Recording User Events or Reason Codes.
- Easy to use. Press Reset. Turn knob to set the desired time. Press Start.
- Subsequent timing cycles. Press Reset. The time previously used will be loaded. Press Start.
- Actual time to build elapsed Timer.
- TAKT Timer to set the pace.
- Green, Yellow and Red warning indicators have preprogrammed default settings, or may be custom programmed by user.
- Four-digit LED seven-segment Display with 4" high digits.
- Count up timer actual timer displays Hour:Min or Min:Sec.
- TAKT timer settable to Hour:Min or Min:Sec.
- Displays may be custom configured to show Target, Actual, Deviation Efficiency, TAKT time, Actual Time and other parameters.
- Made of ruggedized aluminum construction.
- Beeper provides audible sound when TAKT time expires.
- Button to turn beeper on/off.

Displayed parameters

- Target count
- Actual count
- Deviation
- Efficiency
- TAKT time
- Actual time

- Down time
- Changeover time
- Setup time
- Number of times TAKT time was exceeded
- Many others (see manual for details)

In the Box

- DC417B6-PROD1 Production monitor controller with Ethernet.
- KP04B-OC Keypad with four buttons.
- DSP404X4B Quad 4-Digit LED displays with 4" high digits in a common enclosure.
- M6X002F RJ12, Six conductor crossover phone cord, 2ft.
- M4X007F RJ11, Four conductor crossover phone cord, 7ft.
- WT12VAC20VA-RA Wall transformer
- RC Reference guide
- WD Wiring diagram