

# ALZP06



## Product

Production Monitor with TAKT Timer

### Description:

Production monitoring system featuring TAKT Timer/Counter and Quad Display with 4" high digits in a common enclosure. Displays Target, Actual, Deviation and Efficiency.

**Item:** ALZP06

**UPC:** 788581654972

**EAN:** 0788581654972

**Stock Status:** Usually in stock.

**Dimensions:** 27" x 15" x 2.5"

**Weight:** 12.3 lbs.

**MSRP:** \$2,049.00

## Specifications

- Serial data RJ11 connectors for accessories.
- Display has RS422 output with RJ45 connector for accessories.
- Construction: Metal enclosure, black powder coated finish.
- Power requirements: 10-18 VAC or 12-24 VDC power.
- Current consumption: 600ma.
- TMR223B9\_PROD1 Dimensions: 4.5" x 4.5" x 1.25".
- KP04B\_OC Dimensions: 3.5" x 1.75" x 1".
- Quad DSP404B displays in a common enclosure.
- Display Includes Loud Beeper.
- DSP404X4B Dimensions: 27" x 15" x 2.5".
- DSP404X4B Labels: Target, Actual, Deviation, Efficiency.

## Features

- Easy to use. Press Reset. Turn knob to set the desired time. Press Start.
- Subsequent timing cycles. Press Reset. The time previously used will be loaded. Press Start.
- Actual time to build elapsed Timer.
- TAKT Timer to set the pace.
- Green, Yellow and Red warning indicators have preprogrammed default settings, or may be custom programmed by user.
- Four-digit LED seven-segment Display with 4" high digits.
- Count up timer actual timer displays Hour:Min or Min:Sec.
- TAKT timer settable to Hour:Min or Min:Sec.
- Displays may be custom configured to show Target, Actual, Deviation Efficiency, TAKT time, Actual Time and other parameters.
- Made of ruggedized aluminum construction.
- Beeper provides audible sound when TAKT time expires.
- Button to turn beeper on/off.

## In the Box

- TMR223B9-PROD1 Production monitoring TAKT time controller.
- KP04B-OC Keypad with four buttons.
- DSP404X4B Quad 4-Digit LED displays with 4" high digits in a common enclosure.
- M8BK007F 7ft, Cat-5, 8-conductor cable.
- M6X002F RJ12, Six conductor crossover phone cord, 2ft.
- WT12VAC20VA-RA Wall transformer

- RC Reference guide
- WD Wiring diagram