

# KT8IO422A



## Product

8 Bi-Directional RS422 Ports

### Description:

Driver module with eight bi-directional RS422 ports using RJ45 jacks, plastic enclosure.

**Item:** KT8IO422A

**UPC:** 788581653159

**EAN:** 0788581653159

**Stock Status:** Usually in stock.

**Dimensions:** 5.5" x 5.5" x 1.5"

**Weight:** 0.7 lbs.

**MSRP:** \$445.00

## Specifications

- (1) RJ45 jack for RS422 data TX on Blue pair, RX on Green pair.
- (1) RJ45 jack for RS422 data RX on Blue pair, TX on Green pair.
- (1) Power on Brown and Orange pairs.
- (1) Power requirements: 12-15VDC.
- (1) Current drive capability per port: 2 Amps.
- (1) Current drive capability overall: 12 Amps.
- (1) Current consumption: 250mA.

## Features

- (1) Plastic enclosure.
- (1) 8 Bi-directional RS422 ports with RJ45 connectors.

- (1) RS422 Interface drivers to drive multiple Displays from a single power supply.
- (1) Designed to work with Alzatex, Inc. Powered RS422 data ports.
- (1) Power requirements: 10-15VAC or 12-20VDC.

## Item Includes

- (1) KT8IO422A RS422 Driver module.
- (1) RC Reference card
- (1) WD Wiring diagram
- (1) M8BK003F Cable, 3ft, Cat-5
- (1) Not Included: Power supply

## Required Accessories

- (1) PS90W120M6 9-Amp Power Supply with 6-pin Molex connector

## Optional Accessories

- (1) DSP254B Large LED wall display
- (1) DSP256B Large LED wall display
- (1) DSP504B Large LED wall display
- (1) DSP506B Large LED wall display